

Sikkens Autoclear UV

Shine an innovative light on bodyshop profitability

Sikkens Autoclear UV

Sikkens Autoclear UV, the fastest curing clearcoat in the car refinish market. Autoclear UV cures in six minutes and is suitable for any job size

The advantages offered by this clearcoat do not stop at a short drying time. It also uses less material than conventional clearcoats, because of its long potlife and low paint consumption.

When using Autoclear UV you can reduce energy costs by 50% compared to a conventional drying. This can be achieved by one-and-a-half layer application and only 6 minutes bake time!

It delivers excellent results. There is no compromise on the quality of the finish with Autoclear UV.

This product makes repairs invisible, has excellent scratch resistant properties and delivers a superb high gloss finish.




Mixing ratio by weight


100 grams Autoclear UV
150 grams Autoclear UV Hardener
10 grams Autoclear UV Activator



6 minutes by UV light



1½ coat HVLP
(Gravity feed) 1.2 - 1.4



Between coats 2 - 3 min

Features	Benefits
<ul style="list-style-type: none"> ▪ Dry within 6 minutes by UV light 	<ul style="list-style-type: none"> ▪ Reduces energy costs by 50% ▪ Reduced cycle time ▪ Increased productivity and profitability ▪ No re-do jobs due to deformed plastics
<ul style="list-style-type: none"> ▪ Limited Flash-off between coats and before curing 	<ul style="list-style-type: none"> ▪ Reduced cycle time ▪ Increased productivity and profitability
<ul style="list-style-type: none"> ▪ Easy application of 1½ coat 	<ul style="list-style-type: none"> ▪ Easy implementation ▪ Low material consumption
<ul style="list-style-type: none"> ▪ High elasticity 	<ul style="list-style-type: none"> ▪ Reduced stock items. No plasticizer needed.
<ul style="list-style-type: none"> ▪ 8 hours potlife 	<ul style="list-style-type: none"> ▪ Reduced waste of material ▪ Reduced labor time on mixing and cleaning
<ul style="list-style-type: none"> ▪ Very good scratch resistance 	<ul style="list-style-type: none"> ▪ Longer lasting appearance
<ul style="list-style-type: none"> ▪ VOC level of 350 g/l 	<ul style="list-style-type: none"> ▪ Complies with EU VOC legislation

Our focus – your success.